



## DECLARATION OF CONFORMITY

SERANIT GRANIT SERAMİK SAN. TİC. A.Ş., which continuous its at the address of Organize Sanayi Bölgesi – BILECIK / TURKEY,

### HEREBY DECLARES

that the following product is in conformity with the relevant requirement of the Construction Product Directive Council ( Directive 89/106/CE) and the Amending Directive 93/68/EEC.

**Product Type** : Dry Pressed Ceramic Tile - Porcelain Stoneware - Annex G  
E≤%0.5 Group BIa UGL

**Commercial Name** : Matt Unglazed Ceramic Tiles - Porcelain Stoneware

**Intended Use of Product** : Ceramic Tiles Internal and External Floorings /  
Internal and External Wall Finishes

CHARACTERISTICS	UGL
	DECLARED VALUES
	MATT
Reaction to fire	A1fl A1 (Decision 96/03/EC as amended))
Breaking strenght Modules of rupture	>1300 N Min.35 N/mm <sup>2</sup> , Min.a value 32 N/mm <sup>2</sup> TS EN ISO 10545-4
Thermal Shock Resistance	Resistant 10545 - 9
Coefficient of friction ( for pedestrian circulation areas only)	NPD
Skid resistance ( for vehicular circulation areas only)	NPD
Bond strength / adhesion	For cementitious adhesives: ≥0,5N/mm <sup>2</sup> EN 1348 Madde 8.2 For dispersion adhesives: ≥ 1,0 N/mm <sup>2</sup> EN 1324 Madde 7.2 For reaction resin adhesives : ≥ 2,0 N/mm <sup>2</sup> EN 12003 Madde 7.2
Frost Resistance	Resistant TS EN ISO 10545-12
Dangerous Substances *Lead release **Cadmium release	-

**Date :**  
01.01.2007

**General Manager**  
Hamdi ALTUNALAN